


CABLE TAGS MG-TPMF

precut 4mm push in markers, for PMF holders

SerieFLAT MG-TPMF tags are used for marking cables, conduit, tubes, conductors and components. Presented in stem format, tags are simply snapped off their stems and inserted into the appropriate holders. Consult us for other colours.



CERTIFICATES 

 2011/65/EU

LABORATORY TEST 

CEI EN 60950-1

INDELIBILITY

Information technology equipment - Safety

Part 1: General requirements

§ 1.7.11 Durability

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

CEI EN 61010-1

INDELIBILITY

Ed.2 equivalent to VDE 0411-1

Safety indications for electric devices for measurement, control and laboratory use

Part 1: General indications

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

CEMBRE STANDARD

INDELIBILITY

This test was created to simulate cleaning with chemical products commonly used on various surfaces.







By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

DIN 30643

CABLE TAGS MG-TPMF

Technical characteristics

Geometric shape	rectangular easy entry
Precut	yes
Silicon free	yes



CABLE TAGS **MG-TPMF**

List of products

MG-TPMF

Material

UL94 class

Min operating temperature range

Max operating temperature range

Rigid PVC

V0

-22 °F

140 °F

Type	Color	Height	Length	Quantity per sheet	Pack qty	SWcode
42090B	White	0.16 in.	0.39 in.	112	5,600	502
42040B	Yellow	0.16 in.	0.39 in.	112	5,600	502
42000BGY	Grey	0.16 in.	0.39 in.	112	5,600	502
42020B	Red	0.16 in.	0.39 in.	112	5,600	502
42030N	Orange	0.16 in.	0.39 in.	112	5,600	502
42060B	Blue	0.16 in.	0.39 in.	112	5,600	502
42080N	Purple	0.16 in.	0.39 in.	112	5,600	502
42050B	Green	0.16 in.	0.39 in.	112	5,600	502
42010B	Black	0.16 in.	0.39 in.	112	5,600	502
42091B	White	0.16 in.	0.47 in.	80	4,000	505
42041B	Yellow	0.16 in.	0.47 in.	80	4,000	505
42001BGY	Grey	0.16 in.	0.47 in.	80	4,000	505
42021B	Red	0.16 in.	0.47 in.	80	4,000	505
42061B	Blue	0.16 in.	0.47 in.	80	4,000	505
42051B	Green	0.16 in.	0.47 in.	80	4,000	505
42011B	Black	0.16 in.	0.47 in.	80	4,000	505
42092B	White	0.16 in.	0.59 in.	80	4,000	503
42042B	Yellow	0.16 in.	0.59 in.	80	4,000	503
42093B	White	0.16 in.	0.79 in.	64	1,600	504
42043B	Yellow	0.16 in.	0.79 in.	64	1,600	504
42023B	Red	0.16 in.	0.79 in.	64	1,600	504
42063B	Blue	0.16 in.	0.79 in.	64	1,600	504
42053B	Green	0.16 in.	0.79 in.	64	1,600	504
42096B	White	0.16 in.	1.18 in.	48	1,200	509
42046B	Yellow	0.16 in.	1.18 in.	48	1,200	509
42026B	Red	0.16 in.	1.18 in.	48	1,200	509
42066B	Blue	0.16 in.	1.18 in.	48	1,200	509
42056B	Green	0.16 in.	1.18 in.	48	1,200	509
42097B	White	0.16 in.	1.57 in.	32	800	508
42047B	Yellow	0.16 in.	1.57 in.	32	800	508

MG-TPMF-HF

Material Polycarbonate
 UL94 class V0
 Min operating temperature range -40 °F
 Max operating temperature range 266 °F
 Halogen Free yes

Type	Color	Height	Length	Quantity per sheet	Pack qty	SWcode
42090B-HF	White	0.16 in.	0.39 in.	112	5,600	502
42040B-HF	Yellow	0.16 in.	0.39 in.	112	5,600	502
42000B-HF	Metallic grey	0.16 in.	0.39 in.	112	5,600	502
42070B-HF	Brown	0.16 in.	0.39 in.	112	5,600	502
42030N-HF	Orange	0.16 in.	0.39 in.	112	5,600	502
42091B-HF	White	0.16 in.	0.47 in.	80	4,000	505
42041B-HF	Yellow	0.16 in.	0.47 in.	80	4,000	505
42001B-HF	Metallic grey	0.16 in.	0.47 in.	80	4,000	505
42092B-HF	White	0.16 in.	0.59 in.	80	4,000	503
42042B-HF	Yellow	0.16 in.	0.59 in.	80	4,000	503
42002B-HF	Metallic grey	0.16 in.	0.59 in.	80	4,000	503
42093-HF	White	0.16 in.	0.79 in.	64	1,600	504
42043-HF	Yellow	0.16 in.	0.79 in.	64	1,600	504
42096-HF	White	0.16 in.	1.18 in.	48	1,200	509
42046-HF	Yellow	0.16 in.	1.18 in.	48	1,200	509
42097B-HF	White	0.16 in.	1.57 in.	32	800	508
42047B-HF	Yellow	0.16 in.	1.57 in.	32	800	508