


CABLE TIES G V0




CERTIFICATES 

 2011/65/EU

CABLE TIES G V0

Technical characteristics

Min operating temperature range	-40 °F
Max operating temperature range	185 °F
Min operating temperature range (surge)	-40 °F
Max operating temperature range (surge)	248 °F
UL94 class	V0
Material	Polyamide PA6.6



CABLE TIES G V0

List of products

G V0



Type	A	L	Maximum outside diameter	Pack qty	Min. pack qty	Minimum loop tensile strength	Color
G90X2.4 V0	0.09 in.	3.54 in.	0.63 in.	100	1,000	17.6 lbs.	Natural
G100X2.5/M V0	0.1 in.	3.94 in.	0.87 in.	1,000	1,000	17.6 lbs.	Natural
G140X2.5/M V0	0.1 in.	5.51 in.	1.3 in.	1,000	1,000	17.6 lbs.	Natural
G200X2.5/M V0	0.1 in.	7.87 in.	2.09 in.	1,000	1,000	17.6 lbs.	Natural
G150X3.6 V0	0.14 in.	5.91 in.	1.38 in.	100	1,000	39.6 lbs.	Natural
G200X4.8/M V0	0.19 in.	7.87 in.	1.97 in.	1,000	1,000	48.4 lbs.	Natural
G370X4.8 V0	0.19 in.	14.57 in.	4.02 in.	100	100	48.4 lbs.	Natural
G430X4.8 V0	0.19 in.	16.93 in.	4.33 in.	100	100	48.4 lbs.	Natural
G710X9.0 V0	0.35 in.	27.95 in.	7.48 in.	100	100	176 lbs.	Natural

Used with tie

Tags

CABLE AND CONDUIT TAGS MG-ETF - CABLE AND CONDUIT TAGS MG-ETF

LAMINATED WRITE-ON TIE-ON TAGS MS-ETF - LAMINATED WRITE-ON TIE-ON TAGS MS-ETF

DOG TAGS MG-DOG-HF

40205-HF	40206-HF	48300-HF
48340-HF		

MG-DOG.

48203	48204	48244
48300	48320	48322
48340	48341	48342
48352	48380	48391
48392		

Holders

TRANSPARENT HOLDERS PM-DT - TRANSPARENT HOLDERS PM-DT

TRANSPARENT HOLDERS PMF-ET - TRANSPARENT HOLDERS PMF-ET

TRANSPARENT HOLDERS PMT-ET - 54000

TRANSPARENT HOLDERS PM-ET - TRANSPARENT HOLDERS PM-ET

TRANSPARENT HOLDERS PMT-DT

60002	60042
-------	-------

Tags reel

CABLE AND CONDUIT TAGS ETF-ROLL - CABLE AND CONDUIT TAGS ETF-ROLL

Pre-printed

ACCESSORIES FMH - ACCESSORIES FMH

Products used together

Tools

CABLE TIE TOOL 55230 - 5523036090